



DATA SHEET

## Integrated. Efficient. Intelligent. Exos X 5U84



Seagate® Exos™ X 5U84 is the datasphere's ultra-dense, intelligent solution for maximum capacity and performance at an exceptionally low TCO.



### Product Highlights

- Expand a data center seamlessly with single enclosures that host up to 84 drives each and connect up to four enclosures that can host up to 336 drives (6.04PB using 18TB drives). Capacity varies with drives used.
- Efficiently manage hot and cold data with real-time data tiering option
- Deliver unfettered data access with dual redundant controllers capable of achieving up to 7GB/s sequential read, 5.5GB/s sequential write performance
- Rebuild drives faster than ever and reduce downtime with Seagate ADAPT data protection technology
- Opt for replication and snapshot features to meet critical enterprise requirements

### Key Advantages

**Maximum Capacity and Consistent High Performance.** Up to 84 drives in a single 5U enclosure with up to 99.999% high availability and throughputs reaching 7GB/s sequential read and 5.5GB/s sequential write. Easily expand to accommodate data proliferation by connecting up to four Exos X 5U84 systems together for a total of 336 drive slots.

**Cost-Optimized Architecture.** This flexible solution is perfect for businesses with demanding streaming environments that require high read and write throughput while still needing considerable storage space. Built to ensure all space is used to its maximum potential, application access to data is virtually instantaneous, ensuring IT and end users can work efficiently.

**Easy to Set Up, Maintain, and Expand.** All system components—the enclosure, the controller, the firmware, and the drives—are developed and optimized by our engineers to work together seamlessly. This reduces support calls and eliminates technical learning curves. Modular architecture makes components interchangeable between systems, and upgrades are simple due to common FRUs, PCMs, controllers, and software.

**Get Data to Applications Fast and Protect Valuable Assets.** This system is full of features that enable applications to access data with up to a 99.999% availability design. Parallel architecture, multi-core processing, data replication, and fast streaming make access to data unfettered while exclusive Seagate ADAPT data protection technology delivers fast drive rebuilds that virtually eliminate system downtime.

**Build In Security at the Foundation of the Data Life Cycle.** Protect the most valuable business assets with Seagate Secure™ cybersecurity features and intelligent firmware—such as SFTP, SED support, and administrator access controls—that provide built-in security measures for reliable and safe file access, transfer, and management.



| Specifications                     |   |
|------------------------------------|---|
| 4005/5005 Controller Performance   | 7GB/s read throughput   5.5GB/s write throughput  |
| Total BODs                         | Maximum of 4x 5U84 BODs   |
| Advanced Software Features         | Auto-tiering, Snapshots, Asynchronous replication   |
| Base Array Software Features       | Virtual pools, Thin provisioning, ADAPT, SSD read cache, Encryption   |
| High-Availability Features         | Redundant hot-swap controllers   Redundant hot-swap drives, fans, power   Dual power cords   Hot standby spare   Automatic failover   Multi-path support  |
| Device Support                     | SAS HDD   NL-SAS HDD   SAS SSD  |
| Data Protection                    | Seagate ADAPT   RAID levels supported: 0, 1, 3, 5, 6, 10, and 50  |
| System Configuration               | "Up to 84; 3.5" drives per chassis. Connect up to 4 enclosures together totaling 336 drives. E.g. 6.04 PB with 18TB Drives. Capacity varies with drives used."  |
| Physical                           | Height: 222.3mm / 8.75 in   Width: 444.5mm / 17.5 in   Depth: 981mm / 38.63 in   Width w/ear mounts: 483mm / 19.01 in   RBOD weight: 82kg / 180 lb   RBOD weight (with drives): 135kg / 298 lb   EBOD weight: 80kg / 175 lb   EBOD weight (with drives): 130kg / 287 lb                       |
| Hosts                              |   |
| External Ports                     | 8 per system  |
| Fibre Channel Models               | Host speed: 16Gb/s, 8Gb/s Fibre Channel   Interface type: SFP+  |
| iSCSI Models                       | Host speed: 10Gb/s, 1Gb/s iSCSI   Interface type: SFP+  |
| SAS Models                         | Host speed: 12Gb/s, 6Gb/s SAS   Interface type: HD Mini-SAS   |
| System Configuration               |   |
| System Memory                      | 16GB per system (4005), 32GB per system (5005)  |
| Volumes per System                 | 1024  |
| Cache                              | Mirrored cache: Yes   Supercapacitor cache backup: Yes   Cache backup to flash: Yes – nonvolatile   |
| Management                         |   |
| Interface Types                    | 10/100/1000 Ethernet, Mini USB  |
| Protocols Supported                | SNMP, SSL, SSH, SMTP, HTTP(S)   |
| Management Consoles                | Web GUI, CLI  |
| Management Software                | Seagate Systems storage management console   Remote diagnostics   Nondisruptive updates   Volume expansion  |
| Power Requirements—AC Input        |   |
| Input Power Requirements           | 180VAC-240VAC, 50Hz/60Hz  |
| Max Power Output per PSU           | 2200W   |
| Environmental/Temperature Ranges   |   |
| Operating/Nonoperating Temperature | ASHRAE A2, 5°C to 35°C (41°F to 95°F), derate 1°C/300m above 900m, 20°C/hr max rate of change / -40°C to 70°C (-40°F to 158°F)  |
| Operating/Nonoperating Humidity    | -12°C DP and 8% RH to 21°C DP and 80% RH, max DP 21°C / 5% to 100% noncondensing  |
| Operating/Nonoperating Shock       | 5 Gs, 10ms, half sine pulses / 20 Gs, 10ms, half sine pulses  |
| Operating/Nonoperating Vibration   | 0.21 Gs rms 5Hz to 500Hz random / 1.04 Gs rms 2Hz to 200Hz random   |
| Standards/Approvals                |   |
| Safety Certifications              | UL 60950-1 (United States)   CAN/CSA-C22.2 No.60950-1-07 (Canada)   EN 60950-1 (European Union)   IEC 60950-1 (International)   CCC (China PRC – CCC Power Supplies)   BIS (India – BIS Power Supplies)   |
| Ecodesign                          | Commission Regulation (EU) 2019/424 (Directive 2009/125/EC)   |
| Emissions (EMC)                    | FCC CFR 47 Part 15 Subpart B Class A (United States)   ICES/NMB-003 Class A (Canada)   EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 (Europe)   AS/NZS CISPR 32 Class A (Australia/New Zealand)   VCCI Class A (Japan)   KN 32 Class A/KN 35 (S. Korea)   CNS 13438 Class A (Taiwan) |
| Harmonics                          | EN 61000-3-2 (EU)   |
| Flicker                            | EN 61000-3-3 (EU)   |
| Immunity                           | EN 55024 (EU)   KN 24/KN 35 (S. Korea)  |
| Environmental Standards            | The RoHS Directive (2011/65/EU)   The WEEE Directive (2012/19/EU)   The REACH Directive (EC/1907/2006)   The Batteries Directive (2006/66/EC)   |
| Standard Marks/Approvals           | Australia/New Zealand (RCM), Canada (cUL/ICES/NMB-003 Class A), China (CCC – PSU only), European Union (CE), Japan (VCCI), South Korea (KC), Taiwan (BSMI), United States (FCC/UL)  |

© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos, the Exos logo, and Seagate Secure are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and may be controlled for export, import, and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1982.10-2108US August 2021